



KENWORTH OF CENTRAL FLORIDA - ORLANDO (K680)
1800 N. ORANGE BLOSSOM TR
ORLANDO, Florida 32804

CON TECH MANUFACTURING
67079 170TH AVE
DODGE CENTER, Minnesota 55927
United States of America

Eric Johns
Cell Phone: 863-978-8750
Office Phone: 407-425-3170
Email: ejohns@kwcf.net

Dan Welsh
Cell Phone: 507-261-2096
Office Phone: 507-374-2239
Email: danw@ctmmixers.com

Vehicle Summary

Unit		Chassis	
Model:	T880 Series Conventional	Fr Axle Load (lbs):	20000
Type:		Rr Axle Load (lbs):	46000
Description 1:	Conn Expo Donation	G.C.W. (lbs):	80000
Description 2:			
Application		Road Conditions:	
Intended Serv.:	Concrete ready mix: Vehicles which deli	Class A (Highway)	90
Commodity:		Class B (Hwy/Mtn)	10
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	
Type:	Booster axle mixer w/approved frame reinforcement		6
Length (ft):	20	Wheelbase (in):	248
Height (ft):	13.5	Overhang (in):	110
Max Laden Weight (lbs):	4000	Fr Axle to BOC (in):	86
		Cab to Axle (in):	162
		Cab to EOF (in):	272
Trailer		Overall Comb. Length (in):	386
No. of Trailer Axles:	0		
Type:		Special Req.	
Length (ft):	0	U.S. Domestic registry, 50-state.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	120		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Sales Code	Std/Opt	Description	Weight
Model			
0000810	S	T880 Series Conventional	14,844
0070060	S	T880	0
0080066	O	CARB Idle Emissions Reduction - MX	0
0090000	S	Non-Sleeper w/rear axle capacity less than 59K.	0
Engine & Equipment			
0700197	O	PACCAR MX-11 430 2017 430@1600 1650@900 with engine brake N08200 N052 650...IDLE TARGET N09020 N015 NO....ENABLE MX RETARDER IN NEUTRA N08020 N718 155...LRSL SPEED LIMIT N08030 N711 64....MAX PEDAL SPEED N09030 N874 0....ENG BRK DELAY TIME N09040 N871 2.....DSC TGT VEH SPD LMT OFFSET N09050 N870 4.....DSL TGT VEH SPD LIMIT OFFSET N09110 N506 10....CC MIN ENABLE SPD N09130 N890 MT....MULTI TORQUE IN CC N09120 N509 OFF...DYNAMIC CC ENABLE N09220 N690 5.....EIST STANDSTILL IDLE TIME N09230 N689 5.....EIST PARKED MAX IDLE TIME N09240 N692 YES...EIST ENG LOAD RESET N09250 N693 NO....EIST ENG LOAD OVERRIDE N09260 N688 5.....EIST PTO MAX IDLE TIME N09270 N702 YES...EIST OVERRIDE IN PTO MODE N09280 N687 40....EIST AMB AIR TEMP OVERRIDE L N09290 N686 80....EIST AMB AIR TEMP OVERRIDE H N09300 N684 30....EIST CLNT TEMP OVERRIDE LO N09310 N699 YES...EIST ACCEL POSITION RESET N09320 N701 YES...EIST CLUTCH PEDAL RESET N09330 N700 YES...EIST FOOT BRK RESET N09340 N681 YES...EIST PARK BRK RESET ENABLE N09350 N726 1900..FIC MAX ENG SPEED N09400 N545 YES...CAB: ACCEL ACTIVE IN CAB PTO N09410 N578 YES...PTO REM PEDAL ENABLE N09420 N523 6.....CAB: MAX VEH SPD N09430 N520 2000..CAB: MAX ENG SPD - SW CNTRL N09440 N519 2000..CAB: MAX ENG SPD-ACCEL CNTRL N09100 N504 64....CC MAX TARGET SPD N09450 N603 650...CAB: MIN ENG SPD N09510 N535 800...CAB: DEDICATED PRESET "-" N09520 N536 900...CAB: DEDICATED PRESET "+" N09530 N553 2000..REM: MAX ENG SPD-SW/TSC1 CNT N09540 N552 2000..REM: MAX ENG SPD-ACCEL CNTRL N09550 N602 650...REM: MIN ENG SPD N09610 N568 800...REM: DEDICATED PRESET "-" N09620 N569 900...REM: DEDICATED PRESET "+" N09640 N538 750...CAB: CUSTOM PRESET 1	0

Sales Code	Std/Opt	Description	Weight
		N09650 N540 850...CAB: CUSTOM PRESET 2	
		N09660 N542 950...CAB: CUSTOM PRESET 3	
		N09720 N637 3.....MIN SPD FOR DR SHIFT AID	
		N09730 N638 1.....LOWEST TRANS GEAR NUMBER	
		N09740 N639 10....HIGHEST TRANS GEAR NUMBER	
		N09760 N618 5.....DRIVER REWARD VEH SPD BONUS	
		N09770 N621 -5.....DRIVER REWARD VEH SPD PENALT	
		N09670 N571 750...CAB/REM: CUSTOM PRESET 1	
		N09680 N573 850...CAB/REM: CUSTOM PRESET 2	
		N09690 N575 950...CAB/REM: CUSTOM PRESET 3	
		N09360 N071 ON....FIC ENABLE/DISABLE	
		N08000 N717 0.....VSL EXPIRATION DISTANCE	
		N09200 N695 0.....EIST EXPIRATION DISTANCE	
		N09460 N549 ON A..CAB: Park Brake Interlock	
		N09470 N546 ON A..CAB: CLUTCH INTLK	
		N09480 N548 ON A..CAB: NEUTRAL INTLK	
		N09490 N550 ON A..CAB: SER BRK INTLK: PRESS =	
		N09500 N543 DEDIC.CAB: PRESET +/- SW TYPE	
		N09560 N580 ON AD.REM: CLUTCH INTLK	
		N09570 N582 ON AD.REM: NEUTRAL INTLK	
		N09580 N584 ON AD.REM:Ser Brk Intlk:Press=No P	
		N09600 N576 DEDIC.REM: PRESET +/- SW TYPE	
		N09630 N544 TRQ...CAB: ACCEL PEDAL TYPE IN PTO	
		N09800 N541 CNCL..CAB: CUSTOM PRESET 3 FUNC	
		N09750 N632 NONE..OFFSET MODE	
		N09780 N537 CNCL..CAB: CUSTOM PRESET 1 FUNC	
		N09790 N539 CNCL..CAB: CUSTOM PRESET 2 FUNC	
		N09810 N570 CNCL..CAB/REM: CUSTOM PRESET1 FUNC	
		N09820 N572 CNCL..CAB/REM: CUSTOM PRESET2 FUNC	
		N09830 N574 CNCL..CAB/REM: CUSTOM PRESET3 FUNC	
		N09840 N547 OFF...CAB: CUSTOMER INTLK	
		N09700 N581 OFF...REM: CUSTOMER INTLK	
1000151	S	PremierSpec	0
1000204	O	Engine monitoring protection -Derate- PACCAR MX engine parameter.	0
1000243	O	Gearing Analysis: Performance power before economy results.	0
1000251	O	Customer's Typical Operating Spd: 60 MPH.	0
1000282	O	MX Retarder State Cruise Control On Manual Mode Selecting this code will program the engine controller to make manual mode available when cruise control is on, but not set, and the engine brake switch is on. Manual mode means the engine retarder activates whenever the throttle pedal is not depressed. 2013+	0
1000684	O	Effective VSL Setting NA	0
1000858	O	Engine Idle Shutdown Timer Disabled	0
1000891	O	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	0

Sales Code	Std/ Opt	Description	Weight
1006003	S	Air Compressor: WABCO 25.9 CFM PACCAR MX 2017 440cc Air Compressor	0
1051200	S	Air Cleaner: composite firewall mounted PACCAR or Cummins engines	0
1099080	O	Pre-cleaner mounted in the hood plenum	0
1105210	S	Fan hub: Horton 2-Speed for PACCAR MX	0
1123555	S	Cooling module: 1330 square inches. Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant.	0
1247166	S	Exhaust: 2017 EPA RH Under DPF/SCR w/ RH side of cab vertical tailpipe w/ daycabs, extended daycabs, or modular sleepers.	0
1290124	O	Tailpipe: 5 in. single 24 in. 45 degree curved.	-3
1321109	S	Fuel Filter:PACCAR Standard Service Interval Fuel/Water Separator. 2017 and Later Emissions	0
1321200	O	Run Aid:None *For Fuel Filter	0
1321300	S	Start Aid:None *For Fuel Filter	0
1504005	O	Immersion block heater 120V 1500W w/plug under door on C500, T660, T800 & W900.	2
1506055	O	Engine oil pan heater 120V 300W w/plug under door on C500, T660, T800 & W900.	2
1507008	O	Block heater & oil pan heater wired to separate plugs.	0
1816260	S	Alternator: PACCAR 160 amp, brush type	0
1821271	O	Batteries: 2 AGM GP31 threaded post 1850 CCA for T680 and T880 in Cab Battery box only	-50
1836102	S	PACCAR Premium 12V Starter with PACCAR MX Engines PACCAR 12 volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
1840065	S	12V low voltage disconnect for starter battery protection.	0
1900996	O	Jump start terminals under hood.	12
1901018	O	Remote PTO/Throttle, 12-Pin, 250K, Back of Cab OR Back of Sleeper, J1939, Remote Control Provision	0
Transmission & Clutch			
2016169	O	Transmission: Allison World 4700RDS 7-speed with 2-speed reverse w/o retarder, AND w/o PTO provision. 5th generation. Includes shift control, transmission oil temp gauge, oil level sensor & heat exchanger. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.	435
2406453	O	Driveline: 2 Dana SPL250XL 1 centerbearing	95

Sales Code	Std/ Opt	Description	Weight
		requires 3500057 interaxle driveline. Low maintenance offering from Spicer. On-highway 350K mi first service interval, 100K mi subsequent service interval on U-joint, splines lubed for life, quick disconnect end caps.	
2410018	O	Torque converter included w/Allison Transmission.	0
2410151	O	Pushbutton control center console mounted. Class 8 with Allison Transmission.	0
2410244	O	J1939 Park Brake Auto Neutral	0
2410311	O	Decline Allison Neutral at Stop Stand-Alone	0
2410320	O	Allison Fuel Sense 2.0: Basic	0
Front Axle & Equipment			
2517020	O	Meritor MFS20 Front Axle rated 20K 3.5 in. drop, standard track.	150
2607002	S	Front Brakes: 14,601-22K Bendix air disc brakes.	10
2690025	O	Splined rotor for front air disc brakes for use with iron hubs.	0
2702020	O	Front Hubs Iron hub pilot 20,000 lbs. 10 Bolt 16.5x6in. or 7in. or air disc brakes. 10 Bolt, 11-1/4 in. bolt circle. Consider Wheelguards (5850002) with aluminum wheels.	80
2741970	S	ConMet PreSet Plus Hub package; front axle.	0
2750001	S	Hubcap: front vented.	0
2769000	S	Slack Adjusters included w/ front axle or brake. Also use w/ disc brakes.	0
2866025	O	Front Springs: Taperleaf 20K w/ shock absorbers w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins. T880S set forward axle only.	241
2895302	S	Dual power steering gear: 16-22K Sheppard HD94. Heavy duty. Not for use on T3.	73
2899336	S	Power Steering Cooler:Radiator Mounted Air-to-Oil	11
2900616	O	Threaded Bushings for taperleaf spring 16K, 18/20K, 22K, 40K replacing rubber.	0
Rear Axle & Equipment			
3142160	S	Dual Meritor RT46-160 rear axle rated at 46K. Tandem rear axles.	534
3200456	O	Rear Axle Ratio - 4.56.	0
3306001	O	Dual rear Bendix air disc brakes for dual rear axles to 46K capacity.	40
3392604	O	Splined rotor for dual rear air disc brake for use with aluminum hubs.	-208

Sales Code	Std/ Opt	Description	Weight
3407050	S	Dual Rear Hubs: Aluminum hub pilot 46K 11-1/4 in. bolt circle.	0
3441972	S	ConMet PreSet Plus Hub package; dual rear axle.	0
3465900	O	Rear slack adjusters included w/ axle or air disc brakes.	0
3485002	O	Spring brakes included w/ dual rear air disc brakes.	0
3495232	U	Bendix 6S/6M anti-lock brake system w/ air	0
3495238	O	Bendix Side Object Detection System	0
3500057	O	Interaxle driveline 1 Dana SPL170XL	0
3511420	O	Driver Controlled Differential Lock (Crosslock) for Meritor Axles 40K to 52K forward rear & rear rear axle. Under Speed Interlock is standard on T680.	39
3573111	O	Separate switch for dual axles: differential lock or crosslock.	0
3742970	O	Tandem Hendrickson HAULMAAX (HMX) 460 46K. 54 in. axle spacing. With shocks, track rods, rubber bolster bushings and 16.5 in. saddle height. Unladen Height: 10.6 in. Laden Height: 9.5 in.	313
3808119	O	1 Steerable Pusher Watson-Chalin Tru Track 13.5K SL1190SSR Alumilite; includes axle.	1,271
3820050	O	1 Steerable Pusher Disc Brakes And Splined Rotor: Bendix Non-RSD Use With 13.5K Axle	42
3821121	O	1 Steerable pusher hubs aluminum hub pilot for use with 13.5K axle.	0
3828336	O	Pusher or Tag: gauge/switch dash-mounted; gauge and pressure regulator tie-strapped to rail.	0
3830145	O	Delete standard heavy-duty air springs for rear suspension.	0
3832008	O	Heavy-duty torque rods for Hendrickson beam. 46K and under suspensions.	15
3836500	O	Heavy-duty gussets for forward suspension crossmember on Airglide 400/460, Chalmers, or Hendrickson beam suspensions. This replaces the standard gussets.	12
3839046	O	Heavy duty barpin brackets for tandem Hendrickson beam rear suspensions.	0
3841049	O	1st Pusher location: 49 in. from c/l forward tandem axle or single rear axle.	0
Tires & Wheels			
4077533	S	Front tires: Bridgestone M864 425/65R22.5 20PR All Position, On/Off Highway, Wide-base tire.	156
4277487	O	Rear tires: Bridgestone M799 11R22.5 16PR. 42 in. diameter, drive. 19.5 in. SLR. Code is priced per pair of tires.	80
4781796	O	1 steerable pusher: 2 Bridgestone R250ED 255/70R22.5, 16PR; 2-4. 36.7 in. diameter, all position. 17.2 in. SLR.	-38

Sales Code	Std/ Opt	Description	Weight
4900008	O	Rear Tire Quantity: 8	0
5045216	O	Front Wheel: Alcoa 82362 22.5x12.25 aluminum, with Lvl One [TM] finish, hub-pilot mount. 11400lb. maximum rating. Super single. Standard track axles may be over 102 in. w/425 tires. Air disc brake compatible.	-10
5245162	O	Rear Wheel: Alcoa 88367 22.5x8.25 aluminum with Level One [TM] finish, hub-pilot mount. 7400 lb. maximum rating. Air disc brake compatible. Code is priced per pair of wheels.	-176
5781562	O	1 Steerable Pusher Wheel: 2 Alcoa 88367 22.5X8.25; aluminum with Lvl One [TM] finish. Hub-pilot mount. 7400lb. maximum rating.	-44
5854010	O	Single Front Axle: 2 Polished wheels. Polished outboard surface of aluminum wheels.	0
5854012	O	Dual Rear Axle: 4 Polished wheels. Polished outboard surface of outer dual or single aluminum wheels.	0
5854031	O	1 Pusher: 2 Polished wheels. Polished outboard surface of outboard wheels mounted same as front axle. For use on 1 steerable or 1 non-steerable pusher axle with single wheel.	0
5900008	O	Rear Wheel/Rim Quantity: 8	0

Frame & Equipment

6057600	O	Frame Rails: 11-5/8 x 3-7/8 x 3/8 in. Steel to 447 in. Truck frame weight is 3.80 lb.-in. per pair of rails. Section modulus is 21.43, RBM is 2,572,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	680
6302361	O	Bumper: Tapered polished aluminum channel. Requires a bumper setting code.	-6
6319028	O	28 in Bumper setting. Requires a bumper code.	0
6321005	O	Removable Front Tow Hooks: 2.	15
6340009	O	Rear Engine PTO: MX-11, 1.3:1 Drive Ratio Torque Capacity 590 LB-FT Continuous.	48
6340110	O	Side plate on chassis rail for mixer boost-a-load	46
6390103	O	Front mudflaps.	0
6391201	O	Custom Frame Layout: one chassis CFL F/T: Same as 232655 CFL C/M: Last crossmember not to be past 80 inches of tandem	0
6397001	O	Huck bolts throughout frame, where possible.	0
6405000	O	In-cab steel battery box: under rider seat or in stand alone box. Requires appropriate AGM battery code, which varies by model, and appropriate rider seat code be selected prior to entering	-9

Sales Code	Std/ Opt	Description	Weight
		the workscreen. Includes 1 battery disconnect switch.	
6409906	O	In-Cab battery box location: Under rider seat.	0
6451094	O	T470, C5, T6, T8 polished DPF/SCR or CNG cover with step. For use w/ 2010 or later exhaust systems. For T8, use extended length polished battery box on opposite rail to match the length of under cab components.	0
6490095	O	Steel rear intermediate crossmember: One with heavy-duty aluminum gussets, replacing standard.	17
6490120	O	Invert rear intermediate crossmember. A separate sales code is required for one of the following: an additional crossmember; steel crossmember; and if crossmember is not standard aluminum gussets on non-severe service.	0
6721125	O	Delete Mudflap Arms: dealer/customer responsible for installation of arms.	-12
6723000	O	Delete Mudflap Shields-Dealer/Customer responsible for installation of shields.	0
6742009	S	Square end-of-frame w/o crossmember; non-towing.	0
Fuel Tanks & Equip			
7010056	O	Fuel Tank: 56 US gallon 22in. aluminum under replace. Class 8 fuel tank includes an anti-siphon device on the filler neck.	-19
7722011	S	Small round DEF tank. 11 gallons of usable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
7831008	O	6 in. wide lower fuel tank step, for one 22 in. or 24.5 in. tank LH.	2
7840015	O	Polish only one aluminum tank.	0
7840038	O	Polished cover for 1 DEF tank any size.	3
7880009	O	Mechanical anti-roll channel for one tank.	6
7889061	O	Polished stainless steel tank straps for 1 tank.	0
7889203	S	Standard DEF to fuel fill ratio: 2:1 or greater.	0
7889245	S	Anti-siphon device swaged in place. For any number of fuel tanks.	0
7889604	S	DEF tank location is LH.	0
7920056	O	Location: 56 gal fuel tank LH under cab	0
Cab & Equipment			
8025301	S	Cab: Stamped aluminum cab with panoramic curved glass windshield. Standard with stamped aluminum doors, heavy duty	0

Sales Code	Std/Opt	Description	Weight
		in-swinging hinges, and triple sealed doors. Manufactured using self-piercing rivets and structural adhesive. Includes LED exterior marker lights and turn signals.	
8090139	O	Hood: T880 Set-Fwd Short Length W/Mech. Fastened Fenders	0
8098212	O	Bright Engine Air Intake Chrome Trimmed Engine Air Intake on Both Sides of Hood	0
8108011	S	Cab HVAC - Day Cab and 40in Sleeper System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.	0
8201013	S	Steering wheel: 18 in. 4-spoke.	0
8201051	O	Column Mtd Retarder Control, RH Side Use with Manual & Allison Transmissions Only.	0
8201200	S	Adjustable telescoping tilt steering column.	0
8203060	O	5 sets of keys. Replaces standard 2 sets of keys.	0
8205271	O	Dash Mounted - Compact Valve to Actuate Rear Service Brakes Non-Self-Returning.	0
8208495	O	Two spare switches: Wired to power.	0
8220106	O	Gauge: Dash mounted air filter restriction gauge.	0
8221160	O	Gauge: Engine Oil Temperature Gauge With Integral warning light. The NavPlus HD unit includes a virtual engine oil temperature gauge.	0
8222712	O	Gauge: Fuel filter restriction gauge.	0
8222722	O	Gauge: Manifold Pressure Gauge. The NavPlus HD unit includes a virtual manifold pressure gauge.	0
8225658	O	Gauge: Axle oil temperature, dual-drive axle. (2 gauges) w/integral warning light.	0
8282007	S	Kenworth Driver Performance Center:5in Full Color high resolution Thin Film Transistor (TFT) active matrix display with advanced driver information including fuel economy performance, outside air temp, clock, odometer and trip, engine hour meter, ignition timer, engine RPM, general truck information, diagnostics, and gear display. All Highline functionality is accessed via the Kenworth MCS providing intuitive control at the drivers fingertips. Also includes Dark Cabin functionality. When activated, the only interior light that will function when a door is opened is the door courtesy lamp.	0
8282013	S	Kenworth instrumentation and control package with 9 standard easy-read gauges: includes speedometer, tachometer, fuel gauge, engine coolant temp, engine oil pressure, voltmeter, dual air pressure, air application pressure and DEF gauge. All accessory controls utilize electronically activated solenoids that include advanced	0

Sales Code	Std/ Opt	Description	Weight
		vehicle protection interlocks.	
8291011	O	Warning Light and Audible: Drivers Side Seatbelt A telltale and audible warning activates when vehicle speed > 10 mph and driver side seatbelt is not buckled.	0
8300008	S	Interior color: Slate Gray	0
8330102	S	Interior package: Vantage daycab Includes durable headliner and vinyl sidewalls with geometric patterned trim and anodized aluminum accents throughout. Convenient overhead storage cubbies, full size glove box, two center console cupholders, and large door pad map pocket. Standard LH/RH power windows, electric door locks, interior LED lighting, nighttime-friendly red ambient lighting for dash and footwell, and door mounted courtesy light. Includes two standard 12V power outlets. Driver sunvisor includes strap.	0
8390634	S	Rubber floor mat	0
8410194	S	Driver Seat: GT701 HB with DuraSupreme material. The GT701 is standard with a single air bag, scissor linkage seat suspension. It includes a single chamber lumbar support, 10in Fore/Aft adjustment, 7in Up/Down adjustment, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. DR seat standard w/ dual armrests.	0
8480105	O	Rider Seat: GT100 Battery/Utility Box IB DuraSupreme Material. The GT100 seats are standard with fixed base. Includes 3-point matching seat belts.	9
8490187	S	Seat color: Slate Gray with Gray stitching.	0
8496559	O	Driver and Rider Seat Belts: Orange Seat Belts. Replacing standard color.	0
8497005	O	Air line fitting: At driver seat. Customer-installed air chuck.	4
8601423	O	Kenworth Radio with AM/FM/WB/CD/USB, Bluetooth, and Sirius-XM Satellite	4
8601880	O	CB Radio: Cobra 29. Includes weatherband w/header mounted quick release. Includes transceiver & separate speaker remote-mounted in headliner & dual CB antennas. Includes sound tracker & illuminated panel.	11
8698974	O	Base Level Audio System - Daycab:High Performance Door Speakers.	2
8700168	S	Non-self cancelling turn signal: W/column-mounted headlight dimmer switch & intermittent wiper control.	0
8700283	S	LH and RH Trip Ledge Rain Deflectors	0
8700406	O	Stainless steel permit panel on cab, driver side only	0
8700663	S	Kenworth TruckTech+ The Kenworth Remote Diagnostics system provides the Worlds Best reporting of engine and aftertreatment fault codes, as well as enhanced support for the truck owner through rapid communication of fault severity and recommended actions. This option is Standard on all Heavy Duty Kenworths with a PACCAR MX engine, Cummins X15	0

Sales Code	Std/ Opt	Description	Weight
		engine, PX engine or Natural Gas engine. Optional on Medium Duty Kenworths.	
8800260	O	Long grabhandle RH side mounted to side-of-cab exhaust.	2
8800372	O	Grabhandle: LH, Exterior, Side of Cab - Ergonomic Grab Handle Mounted To The Left Hand Exterior Of The Cab For Entry and Exit.	3
8800402	S	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles	0
8832113	S	Kenworth Daylite Door with standard LH/RH electric door locks and LH/RH electric window controls.	0
8841411	S	Single air horn under cab.	0
8850139	S	Look-Down, Pass. Door, Black 11x6	0
8865003	O	Aero Mirror: Dual Kenworth Chrome Aero. Motorized Heated Mirrors, 7in X 13in With Chrome Mirror Shell and Black Mirror Arms. Also Includes LH/RH Heated 6in X 7in Convex Mirrors. Mirror Brackets Set For 8-1/2 ft Load Width. Mirror Controls Located On Driver Side Door Pad.	0
8871446	S	Rear cab stationary window 19in x 36in	0
8879917	O	Two additional outboard windows 19in x 12in	10
8890101	S	One-piece bonded-in windshield with curved glass. Standard.	0
8890135	S	Exterior stainless steel sunvisor.	19
8890348	O	Wheelwell Fender Extension: 4.5 inches	0
8890876	S	Kenworth Cab/Sleeper Air Suspension.	0
8891013	O	Extreme Temperature Insulation: Daycab Additional cab side wall insulation with improved material properties over standard insulation package.	0
Lights & Instruments			
9010553	S	Headlamps: SAE Dual Halogen Complex Reflector	0
9022137	S	Marker Lights: Five, rectangular, LED	0
9030016	S	Turn Signal Lights: Flush mounted LED mounted at top of fender wheel arc	0
9030052	S	LED Stop, Turn, Tail: With Two LED Backup Lights and With An LED License Plate.	0
9056140	O	Dual Pedestal Floodlights: First Set	2
9059901	O	Floodlight Location: Located High - First Set. This Code To Be Used With Flush-Mount (9052011) or C/I (9058071) Codes Only.	0

Sales Code	Std/ Opt	Description	Weight
9060055	O	Halogen Spotlight: LH & RH mounted. T680 and T880 models include dash switch for RH spot lamp as standard.	11
9090039	S	Marker Lights: Interrupter Switch. Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash.	0
9090142	O	Wiring Only: For customer-installed backup alarm.	0
9090849	O	Polyswitches replacing fuses. Switch will automatically reset after removal of excess load.	0
Air Equipment			
9101235	O	Air Dryer: Bendix AD-IS Extended Purge heated. with PuraGuard	4
9108001	S	Moisture ejection valve w/ pull cable drain.	0
9140020	S	Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing.	0
9140085	O	Bendix LQ-5 ratio valve:for Kenworth-installed pusher/tag. LQ-5 valve limits the amount of air applied to the pusher brakes. Helps prevent lockup in lightly loaded conditions.	2
9140092	O	Schrader valve to charge air system.	2
Extended Warranty			
9200006	O	Base Warranty - PACCAR MX-11 & MX-13 Engine 24 months / 250,000 miles / 400,000 km / 6250 hours.	0
9200021	S	Base Warranty - Standard Service Heavy Duty 12 months / 100,000 miles / 160,000 km.	0
9202809	O	EW: US Basic Vehicle 5 year/200,000 miles, United States only.	0
9202878	O	EW: US Towing For Warrantable Failures 5 year / Unlimited miles. For use w/ Kenworth & PACCAR Extended Warranty.	0
9207107	O	PACCAR MX Premium Coverage: <460HP 5yr/200k mi (320k km) EPA17	0
9207182	O	PACCAR MX Aftertreatment: Use w/ Premium <460HP 5yr/200k mi (320k km) EPA17	0
Miscellaneous			
9400073	O	Ship to Specific Address. Con-Tech Manufacturing INC 67079 170TH AVE Dodge Center, Minnesota, 55927 United States of America	0
9409852	O	GHG Secondary Manufacturer: Does Not Apply	0
9490003	O	Additional lead time required for off highway & /or specialty component truck.	0
9490206	O	Warning triangle reflector kit: Shipped loose.	4

Sales Code	Std/ Opt	Description	Weight
		Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	
9490408	O	One 5 lb. dry chemical type fire extinguisher mounted inboard of rider seat. Class ABC.	11
9491665	S	CECU/VECU Electronics Architecture	0

Promotions

Paint

9700000	O	Paint color number(s).	0
9943004	O	Bumper Unpainted	0
9943050	O	Day Cab Standard Paint	0
9944820	O	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0

Order Comments

Total Weight

18,411

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information